



| MACHINE DIMENSIONS                    | 6MDX                |                  | 9MDX                |                  |
|---------------------------------------|---------------------|------------------|---------------------|------------------|
|                                       | STRAIGHT mm (ft in) | SWING mm (ft in) | STRAIGHT mm (ft in) | SWING mm (ft in) |
| <b>A</b> Overall length               | 4452 (14'7")        | 4710 (15'5")     | 4585 (15'1")        | 4734 (15'6")     |
| <b>B</b> Overall width                | 2300 (7'7")         | 2211 (7'3")      | 2502 (8'3")         | 2364 (7'9")      |
| <b>C</b> Overall height               | 2875 (9'5")         | 2875 (9'5")      | 3384 (11'1")        | 3384 (11'1")     |
| <b>D</b> Wheelbase                    | 2450 (8')           | 2450 (8')        | 2450 (8')           | 2450 (8')        |
| <b>E</b> Height to skip lip           | 1546 (5'1")         | 1690 (5'7")      | 1682 (5'6")         | 1827 (5'11")     |
| <b>F</b> Height to back of skip       | 1998 (6'7")         | 2167 (7'1")      | 2292 (7'6")         | 2483 (8'2")      |
| <b>G</b> Height to first step         | 472 (1'7")          | 472 (1'7")       | 509 (1'8")          | 509 (1'8")       |
| <b>H</b> Additional height for beacon | 140 (5.5")          | 140 (5.5")       | 140 (5.5")          | 140 (5.5")       |
| <b>I</b> Ground Clearance             | 347 (1'2")          | 347 (1'2")       | 396 (1'4")          | 396 (1'4")       |